



Australian Government  
Australian Signals Directorate



[Pumili ng Wika](#)

Menu

Search 

---

[< Previous level](#)

# Essential Eight Maturity Model

Content complexity

**Moderate**

## Content written for



Small & medium business



Large organisations & infrastructure



Government

## Attachments



**PROTECT - Essential Eight Maturity Model (November 2022)**

1.04MB .pdf

Report a cybercrime, cyber security incident or vulnerability.



Report

[Back to top](#)

# Introduction

The Australian Cyber Security Centre (ACSC) has developed prioritised mitigation strategies, in the form of the [Strategies to Mitigate Cyber Security Incidents](#), to help organisations protect themselves against various cyber threats. The most effective of these mitigation strategies are the Essential Eight.

The Essential Eight has been designed to protect Microsoft Windows-based internet-connected networks. While the principles behind the Essential Eight may be applied to cloud services and enterprise mobility, or other operating systems, it was not primarily designed for such purposes and alternative mitigation strategies may be more appropriate to mitigate unique cyber threats to these environments. In such cases, organisations should consider alternative guidance provided by the ACSC.

The [Essential Eight Maturity Model](#), first published in June 2017 and updated regularly, supports the implementation of the Essential Eight. It is based on the ACSC's experience in producing cyber threat intelligence, responding to cyber incidents, conducting penetration testing and assisting organisations to implement the Essential Eight.

# Implementation

When implementing the Essential Eight, organisations should identify and plan for a target maturity level suitable for their environment. Organisations should then progressively implement each maturity level until that target is achieved.

As the mitigation strategies that constitute the Essential Eight have been designed to complement each other, and to provide coverage of various cyber threats, organisations should plan their implementation to achieve the same maturity level across all eight mitigation strategies before moving onto higher maturity levels.

Organisations should implement the Essential Eight using a risk-based approach. In doing so,

[Report a cybercrime, cyber security incident or vulnerability.](#)



Report

monitored and reviewed on a regular basis. Note, the appropriate use of exceptions should not preclude an organisation from being assessed as meeting the requirements for a given maturity level.

As the Essential Eight outlines a minimum set of preventative measures, organisations need to implement additional measures to those within this maturity model where it is warranted by their environment. Further, while the Essential Eight can help to mitigate the majority of cyber threats, it will not mitigate all cyber threats. As such, additional mitigation strategies and controls need to be considered, including those from the [Strategies to Mitigate Cyber Security Incidents](#) and the [Information Security Manual](#).

Finally, there is no requirement for organisations to have their Essential Eight implementation certified by an independent party. However, Essential Eight implementations may need to be assessed by an independent party if required by a government directive or policy, by a regulatory authority, or as part of contractual arrangements.

## Maturity levels

To assist organisations with their implementation of the Essential Eight, four maturity levels have been defined (Maturity Level Zero through to Maturity Level Three). With the exception of Maturity Level Zero, the maturity levels are based on mitigating increasing levels of tradecraft (i.e. tools, tactics, techniques and procedures) and targeting, which are discussed in more detail below. Depending on overall capability, malicious actors may exhibit different levels of tradecraft for different operations against different targets. For example, malicious actors capable of advanced tradecraft may use it against one target while using basic tradecraft against another. As such, organisations should consider what level of tradecraft and targeting, rather than which malicious actors, they are aiming to mitigate.

Organisations need to consider that the likelihood of being targeted is influenced by their desirability to malicious actors, and the consequences of a cyber incident will depend on their requirement for the confidentiality of their data, as well as their requirement for the availability and integrity of their systems and data. This, in combination with the descriptions for each maturity level, can be used to help determine a target maturity level to implement.

[Report a cybercrime, cyber security incident or vulnerability.](#)



Report

remainder of the mitigation strategies from the [Strategies to Mitigate Cyber Security Incidents](#) and the [Information Security Manual](#).

## Maturity Level Zero

This maturity level signifies that there are weaknesses in an organisation's overall cyber security posture. When exploited, these weaknesses could facilitate the compromise of the confidentiality of their data, or the integrity or availability of their systems and data, as described by the tradecraft and targeting in Maturity Level One below.

## Maturity Level One

The focus of this maturity level is malicious actors who are content to simply leverage commodity tradecraft that is widely available in order to gain access to, and likely control of, systems. For example, malicious actors opportunistically using a publicly-available exploit for a vulnerability in an internet-facing service which had not been patched, or authenticating to an internet-facing service using credentials that were stolen, reused, brute forced or guessed.

Generally, malicious actors are looking for any victim rather than a specific victim and will opportunistically seek common weaknesses in many targets rather than investing heavily in gaining access to a specific target. Malicious actors will employ common social engineering techniques to trick users into weakening the security of a system and launch malicious applications, for example via Microsoft Office macros. If accounts that malicious actors compromise have special privileges they will exploit it. Depending on their intent, malicious actors may also destroy data (including backups).

## Maturity Level Two

The focus of this maturity level is malicious actors operating with a modest step-up in capability from the previous maturity level. These malicious actors are willing to invest more time in a target and, perhaps more importantly, in the effectiveness of their tools. For example, these malicious actors will likely employ well-known tradecraft in order to better attempt to bypass controls implemented by a target and evade detection. This includes actively targeting credentials using phishing and employing technical and social engineering techniques to circumvent weak multi-factor authentication.

Report a cybercrime, cyber security incident or vulnerability.



Report

invest time to ensure their phishing is effective and employ common social engineering techniques to trick users to weaken the security of a system and launch malicious applications, for example via Microsoft Office macros. If accounts that malicious actors compromise have special privileges they will exploit it, otherwise they will seek accounts with special privileges. Depending on their intent, malicious actors may also destroy all data (including backups) accessible to an account with special privileges.

## Maturity Level Three

The focus of this maturity level is malicious actors who are more adaptive and much less reliant on public tools and techniques. These malicious actors are able to exploit the opportunities provided by weaknesses in their target's cyber security posture, such as the existence of older software or inadequate logging and monitoring. Malicious actors do this to not only extend their access once initial access has been gained to a target, but to evade detection and solidify their presence. Malicious actors make swift use of exploits when they become publicly available as well as other tradecraft that can improve their chance of success.

Generally, malicious actors may be more focused on particular targets and, more importantly, are willing and able to invest some effort into circumventing the idiosyncrasies and particular policy and technical controls implemented by their targets. For example, this includes social engineering a user to not only open a malicious document but also to unknowingly assist in bypassing controls. This can also include circumventing stronger multi-factor authentication by stealing authentication token values to impersonate a user. Once a foothold is gained on a system, malicious actors will seek to gain privileged credentials or password hashes, pivot to other parts of a network, and cover their tracks. Depending on their intent, malicious actors may also destroy all data (including backups).

## Requirements for each maturity level

Requirements for Maturity Level One through to Maturity Level Three are outlined in Appendices A to C. A comparison of the maturity levels, with changes between maturity levels indicated via bolded text, is outlined in Appendix D.

## Further information

Report a cybercrime, cyber security incident or vulnerability.



Report

- Additional mitigation strategies are available in the [Strategies to Mitigate Cyber Security Incidents](#) publication.
- Further Information on implementing application control is available in the [Implementing Application Control](#) publication.
- Further Information on patching is available in the [Assessing Vulnerabilities and Applying Patches](#) publication.
- Further Information on controlling Microsoft Office macros is available in the [Microsoft Office Macro Security](#) publication.
- Further Information on controlling privileged accounts is available in the [Restricting Administrator Privileges](#) publication.
- Further Information on implementing multi-factor authentication is available in the [Implementing Multi-Factor Authentication](#) publication.

## Contact details

If you have any questions regarding this guidance you can [write to us](#) or call us on 1300 CYBER1 (1300 292 371).

## Appendix A: Maturity Level One

Mitigation Strategy	Description
<b>Application control</b>	The execution of executables, software libraries, scripts, installers, compiled HTML, HTML applications and control panel applets is prevented on workstations from within standard user profiles and temporary folders used by the operating system, web browsers and email clients.

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>A vulnerability scanner with an up-to-date vulnerability database is used for vulnerability scanning activities.</p> <p>A vulnerability scanner is used at least daily to identify missing patches or updates for vulnerabilities in internet-facing services.</p> <p>A vulnerability scanner is used at least fortnightly to identify missing patches or updates for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in internet-facing services are applied within two weeks of release, or within 48 hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products are applied within one month of release.</p> <p>Internet-facing services, office productivity suites, web browsers and their extensions, email clients, PDF software, Adobe Flash Player, and security products that are no longer supported by vendors are removed.</p>
<p><b>Configure Microsoft Office macro settings</b></p>	<p>Microsoft Office macros are disabled for users that do not have a demonstrated business requirement.</p> <p>Microsoft Office macros in files originating from the internet are</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

<b>Mitigation Strategy</b>	<b>Description</b>
	Microsoft Office macro security settings cannot be changed by users.
<b>User application hardening</b>	<p>Web browsers do not process Java from the internet.</p> <p>Web browsers do not process web advertisements from the internet.</p> <p>Internet Explorer 11 does not process content from the internet.</p> <p>Web browser security settings cannot be changed by users.</p>
<b>Restrict administrative privileges</b>	<p>Requests for privileged access to systems and applications are validated when first requested.</p> <p>Privileged accounts (excluding privileged service accounts) are prevented from accessing the internet, email and web services.</p> <p>Privileged users use separate privileged and unprivileged operating environments.</p> <p>Unprivileged accounts cannot logon to privileged operating environments.</p> <p>Privileged accounts (excluding local administrator accounts) cannot logon to unprivileged operating environments.</p>
<b>Patch operating systems</b>	An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>A vulnerability scanner is used at least daily to identify missing patches or updates for vulnerabilities in operating systems of internet-facing services.</p> <p>A vulnerability scanner is used at least fortnightly to identify missing patches or updates for vulnerabilities in operating systems of workstations, servers and network devices.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of internet-facing services are applied within two weeks of release, or within 48 hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of workstations, servers and network devices are applied within one month of release.</p> <p>Operating systems that are no longer supported by vendors are replaced.</p>
<p><b>Multi-factor authentication</b></p>	<p>Multi-factor authentication is used by an organisation's users when they authenticate to their organisation's internet-facing services.</p> <p>Multi-factor authentication is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their organisation's sensitive data.</p> <p>Multi-factor authentication (where available) is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>Multi-factor authentication is enabled by default for an organisation's non-organisational users (but they can choose to opt out) when they authenticate to the organisation's internet-facing services.</p>
<p><b>Regular backups</b></p>	<p>Backups of important data, software and configuration settings are performed and retained with a frequency and retention timeframe in accordance with business continuity requirements.</p> <p>Backups of important data, software and configuration settings are synchronised to enable restoration to a common point in time.</p> <p>Backups of important data, software and configuration settings are retained in a secure and resilient manner.</p> <p>Restoration of important data, software and configuration settings from backups to a common point in time is tested as part of disaster recovery exercises.</p> <p>Unprivileged accounts cannot access backups belonging to other accounts.</p> <p>Unprivileged accounts are prevented from modifying and deleting backups.</p>

## Appendix B: Maturity Level Two

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
<p><b>Application control</b></p>	<p>Application control is implemented on workstations and internet-facing servers.</p> <p>Application control restricts the execution of executables, software libraries, scripts, installers, compiled HTML, HTML applications and control panel applets to an organisation-approved set.</p> <p>Allowed and blocked execution events on workstations and internet-facing servers are logged.</p>
<p><b>Patch applications</b></p>	<p>An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability scanning activities.</p> <p>A vulnerability scanner with an up-to-date vulnerability database is used for vulnerability scanning activities.</p> <p>A vulnerability scanner is used at least daily to identify missing patches or updates for vulnerabilities in internet-facing services.</p> <p>A vulnerability scanner is used at least weekly to identify missing patches or updates for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products.</p> <p>A vulnerability scanner is used at least fortnightly to identify missing patches or updates for vulnerabilities in other applications.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>Patches, updates or vendor mitigations for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products are applied within two weeks of release.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in other applications are applied within one month of release.</p> <p>Internet-facing services, office productivity suites, web browsers and their extensions, email clients, PDF software, Adobe Flash Player, and security products that are no longer supported by vendors are removed.</p>
<p><b>Configure Microsoft Office macro settings</b></p>	<p>Microsoft Office macros are disabled for users that do not have a demonstrated business requirement.</p> <p>Microsoft Office macros in files originating from the internet are blocked.</p> <p>Microsoft Office macro antivirus scanning is enabled.</p> <p>Microsoft Office macros are blocked from making Win32 API calls.</p> <p>Microsoft Office macro security settings cannot be changed by users.</p> <p>Allowed and blocked Microsoft Office macro execution events are logged.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>Web browsers do not process web advertisements from the internet.</p> <p>Internet Explorer 11 does not process content from the internet.</p> <p>Web browser security settings cannot be changed by users.</p> <p>Microsoft Office is blocked from creating child processes.</p> <p>Microsoft Office is blocked from creating executable content.</p> <p>Microsoft Office is blocked from injecting code into other processes.</p> <p>Microsoft Office is configured to prevent activation of OLE packages.</p> <p>Microsoft Office security settings cannot be changed by users.</p> <p>PDF software is blocked from creating child processes.</p> <p>PDF software security settings cannot be changed by users.</p> <p>ACSC or vendor hardening guidance for web browsers, Microsoft Office and PDF software is implemented.</p> <p>Blocked PowerShell script execution events are logged.</p>
<p><b>Restrict administrative privileges</b></p>	<p>Requests for privileged access to systems and applications are validated when first requested.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>Privileged access to systems and applications is automatically disabled after 45 days of inactivity.</p> <p>Privileged accounts (excluding privileged service accounts) are prevented from accessing the internet, email and web services.</p> <p>Privileged users use separate privileged and unprivileged operating environments.</p> <p>Privileged operating environments are not virtualised within unprivileged operating environments.</p> <p>Unprivileged accounts cannot logon to privileged operating environments.</p> <p>Privileged accounts (excluding local administrator accounts) cannot logon to unprivileged operating environments.</p> <p>Administrative activities are conducted through jump servers.</p> <p>Credentials for local administrator accounts and service accounts are long, unique, unpredictable and managed.</p> <p>Privileged access events are logged.</p> <p>Privileged account and group management events are logged.</p>
<p><b>Patch operating systems</b></p>	<p>An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability scanning activities</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>A vulnerability scanner is used at least daily to identify missing patches or updates for vulnerabilities in operating systems of internet-facing services.</p> <p>A vulnerability scanner is used at least weekly to identify missing patches or updates for vulnerabilities in operating systems of workstations, servers and network devices.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of internet-facing services are applied within two weeks of release, or within 48 hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of workstations, servers and network devices are applied within two weeks of release.</p> <p>Operating systems that are no longer supported by vendors are replaced.</p>
<p><b>Multi-factor authentication</b></p>	<p>Multi-factor authentication is used by an organisation's users when they authenticate to their organisation's internet-facing services.</p> <p>Multi-factor authentication is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their organisation's sensitive data.</p> <p>Multi-factor authentication (where available) is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>opt out) when they authenticate to the organisation's internet-facing services.</p> <p>Multi-factor authentication is used to authenticate privileged users of systems.</p> <p>Multi-factor authentication uses either: something users have and something users know, or something users have that is unlocked by something users know or are.</p> <p>Successful and unsuccessful multi-factor authentication events are logged.</p>
<p><b>Regular backups</b></p>	<p>Backups of important data, software and configuration settings are performed and retained with a frequency and retention timeframe in accordance with business continuity requirements.</p> <p>Backups of important data, software and configuration settings are synchronised to enable restoration to a common point in time.</p> <p>Backups of important data, software and configuration settings are retained in a secure and resilient manner.</p> <p>Restoration of important data, software and configuration settings from backups to a common point in time is tested as part of disaster recovery exercises.</p> <p>Unprivileged accounts cannot access backups belonging to other accounts.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>Unprivileged accounts are prevented from modifying and deleting backups.</p> <p>Privileged accounts (excluding backup administrator accounts) are prevented from modifying and deleting backups.</p>

## Appendix C: Maturity Level Three

Mitigation Strategy	Description
<p><b>Application control</b></p>	<p>Application control is implemented on workstations and servers.</p> <p>Application control restricts the execution of executables, software libraries, scripts, installers, compiled HTML, HTML applications, control panel applets and drivers to an organisation-approved set.</p> <p>Microsoft's 'recommended block rules' are implemented.</p> <p>Microsoft's 'recommended driver block rules' are implemented.</p> <p>Application control rulesets are validated on an annual or more frequent basis.</p> <p>Allowed and blocked execution events on workstations and servers are centrally logged.</p> <p>Event logs are protected from unauthorised modification and</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy <b>Patch applications</b>	Description
	<p>An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability scanning activities.</p> <p>A vulnerability scanner with an up-to-date vulnerability database is used for vulnerability scanning activities.</p> <p>A vulnerability scanner is used at least daily to identify missing patches or updates for vulnerabilities in internet-facing services.</p> <p>A vulnerability scanner is used at least weekly to identify missing patches or updates for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products.</p> <p>A vulnerability scanner is used at least fortnightly to identify missing patches or updates for vulnerabilities in other applications.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in internet-facing services are applied within two weeks of release, or within 48 hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products are applied within two weeks of release, or within 48 hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in other applications are applied within one month of release.</p> <p>Applications that are no longer supported by vendors are removed.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
<b>settings</b>	<p>Only Microsoft Office macros running from within a sandboxed environment, a Trusted Location or that are digitally signed by a trusted publisher are allowed to execute.</p> <p>Only privileged users responsible for validating that Microsoft Office macros are free of malicious code can write to and modify content within Trusted Locations.</p> <p>Microsoft Office macros digitally signed by an untrusted publisher cannot be enabled via the Message Bar or Backstage View.</p> <p>Microsoft Office's list of trusted publishers is validated on an annual or more frequent basis.</p> <p>Microsoft Office macros in files originating from the internet are blocked.</p> <p>Microsoft Office macro antivirus scanning is enabled.</p> <p>Microsoft Office macros are blocked from making Win32 API calls.</p> <p>Microsoft Office macro security settings cannot be changed by users.</p> <p>Allowed and blocked Microsoft Office macro execution events are centrally logged.</p> <p>Event logs are protected from unauthorised modification and deletion.</p> <p>Event logs are monitored for signs of compromise and actioned</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
<p><b>User application hardening</b></p>	<p>Web browsers do not process Java from the internet.</p> <p>Web browsers do not process web advertisements from the internet.</p> <p>Internet Explorer 11 is disabled or removed.</p> <p>Web browser security settings cannot be changed by users.</p> <p>Microsoft Office is blocked from creating child processes.</p> <p>Microsoft Office is blocked from creating executable content.</p> <p>Microsoft Office is blocked from injecting code into other processes.</p> <p>Microsoft Office is configured to prevent activation of OLE packages.</p> <p>Microsoft Office security settings cannot be changed by users.</p> <p>PDF software is blocked from creating child processes.</p> <p>PDF software security settings cannot be changed by users.</p> <p>ACSC or vendor hardening guidance for web browsers, Microsoft Office and PDF software is implemented.</p> <p>.NET Framework 3.5 (includes .NET 2.0 and 3.0) is disabled or removed.</p> <p>Windows PowerShell 2.0 is disabled or removed.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>Event logs are protected from unauthorised modification and deletion.</p> <p>Event logs are monitored for signs of compromise and actioned when any signs of compromise are detected.</p>
<p><b>Restrict administrative privileges</b></p>	<p>Requests for privileged access to systems and applications are validated when first requested.</p> <p>Privileged access to systems and applications is automatically disabled after 12 months unless revalidated.</p> <p>Privileged access to systems and applications is automatically disabled after 45 days of inactivity.</p> <p>Privileged access to systems and applications is limited to only what is required for users and services to undertake their duties.</p> <p>Privileged accounts are prevented from accessing the internet, email and web services.</p> <p>Privileged users use separate privileged and unprivileged operating environments.</p> <p>Privileged operating environments are not virtualised within unprivileged operating environments.</p> <p>Unprivileged accounts cannot logon to privileged operating environments.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>Just-in-time administration is used for administering systems and applications.</p> <p>Administrative activities are conducted through jump servers.</p> <p>Credentials for local administrator accounts and service accounts are long, unique, unpredictable and managed.</p> <p>Windows Defender Credential Guard and Windows Defender Remote Credential Guard are enabled.</p> <p>Privileged access events are centrally logged.</p> <p>Privileged account and group management events are centrally logged.</p> <p>Event logs are protected from unauthorised modification and deletion.</p> <p>Event logs are monitored for signs of compromise and actioned when any signs of compromise are detected.</p>
<p><b>Patch operating systems</b></p>	<p>An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability scanning activities.</p> <p>A vulnerability scanner with an up-to-date vulnerability database is used for vulnerability scanning activities.</p> <p>A vulnerability scanner is used at least daily to identify missing</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

<b>Mitigation Strategy</b>	<b>Description</b>
	<p>A vulnerability scanner is used at least weekly to identify missing patches or updates for vulnerabilities in operating systems of workstations, servers and network devices.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of internet-facing services are applied within two weeks of release, or within 48 hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of workstations, servers and network devices are applied within two weeks of release, or within 48 hours if an exploit exists.</p> <p>The latest release, or the previous release, of operating systems are used.</p> <p>Operating systems that are no longer supported by vendors are replaced.</p>
<b>Multi-factor authentication</b>	<p>Multi-factor authentication is used by an organisation's users when they authenticate to their organisation's internet-facing services.</p> <p>Multi-factor authentication is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their organisation's sensitive data.</p> <p>Multi-factor authentication (where available) is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>out) when they authenticate to the organisation's internet-facing services.</p> <p>Multi-factor authentication is used to authenticate privileged users of systems.</p> <p>Multi-factor authentication is used to authenticate users accessing important data repositories.</p> <p>Multi-factor authentication is phishing-resistant and uses either: something users have and something users know, or something users have that is unlocked by something users know or are.</p> <p>Successful and unsuccessful multi-factor authentication events are centrally logged.</p> <p>Event logs are protected from unauthorised modification and deletion.</p> <p>Event logs are monitored for signs of compromise and actioned when any signs of compromise are detected.</p>
<p><b>Regular backups</b></p>	<p>Backups of important data, software and configuration settings are performed and retained with a frequency and retention timeframe in accordance with business continuity requirements.</p> <p>Backups of important data, software and configuration settings are synchronised to enable restoration to a common point in time.</p> <p>Backups of important data, software and configuration settings are</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Mitigation Strategy	Description
	<p>Restoration of important data, software and configuration settings from backups to a common point in time is tested as part of disaster recovery exercises.</p> <p>Unprivileged accounts cannot access backups belonging to other accounts, nor their own accounts.</p> <p>Privileged accounts (excluding backup administrator accounts) cannot access backups belonging to other accounts, nor their own accounts.</p> <p>Unprivileged accounts are prevented from modifying and deleting backups.</p> <p>Privileged accounts (including backup administrator accounts) are prevented from modifying and deleting backups during their retention period.</p>

## Appendix D: Comparison of maturity levels

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
<p><b>Application control</b></p>	<p>The execution of executables, software libraries, scripts, installers, compiled HTML</p>	<p><b>Application control is implemented on workstations and internet-facing servers</b></p>	<p>Application control is implemented on workstations and <b>servers.</b></p>

Report a cybercrime, cyber security incident or vulnerability.



Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
	<p>on workstations from within standard user profiles and temporary folders used by the operating system, web browsers and email clients.</p>	<p>execution of executables, software libraries, scripts, installers, compiled HTML, HTML applications and control panel applets <b>to an organisation-approved set.</b></p> <p><b>Allowed and blocked execution events on workstations and internet-facing servers are logged.</b></p>	<p>software libraries, scripts, installers, compiled HTML, HTML applications, control panel applets <b>and drivers</b> to an organisation-approved set.</p> <p><b>Microsoft's 'recommended block rules' are implemented.</b></p> <p><b>Microsoft's 'recommended driver block rules' are implemented.</b></p> <p><b>Application control rulesets are validated on an annual or more frequent basis.</b></p> <p>Allowed and blocked execution events on workstations and <b>servers</b> are <b>centrally</b> logged.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
			<p><b>modification and deletion.</b></p> <p><b>Event logs are monitored for signs of compromise and actioned when any signs of compromise are detected.</b></p>
<p><b>Patch applications</b></p>	<p>An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability scanning activities.</p> <p>A vulnerability scanner with an up-to-date vulnerability database is used for vulnerability scanning activities.</p> <p>A vulnerability</p>	<p>An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability scanning activities.</p> <p>A vulnerability scanner with an up-to-date vulnerability database is used for vulnerability scanning activities.</p> <p>A vulnerability</p>	<p>An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability scanning activities.</p> <p>A vulnerability scanner with an up-to-date vulnerability database is used for vulnerability scanning activities.</p> <p>A vulnerability</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
	<p>vulnerabilities in internet-facing services.</p> <p>A vulnerability scanner is used at least fortnightly to identify missing patches or updates for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in internet-facing services are applied within two weeks of release, or within 48 hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in</p>	<p>vulnerabilities in internet-facing services.</p> <p>A vulnerability scanner is used at least <b>weekly</b> to identify missing patches or updates for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products.</p> <p><b>A vulnerability scanner is used at least fortnightly to identify missing patches or updates for vulnerabilities in other applications.</b></p> <p>Patches, updates or vendor mitigations for vulnerabilities in internet-facing</p>	<p>vulnerabilities in internet-facing services.</p> <p>A vulnerability scanner is used at least weekly to identify missing patches or updates for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products.</p> <p>A vulnerability scanner is used at least fortnightly to identify missing patches or updates for vulnerabilities in other applications.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in internet-facing services are applied</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
	<p>software, and security products are applied within one month of release.</p> <p>Internet-facing services, office productivity suites, web browsers and their extensions, email clients, PDF software, Adobe Flash Player, and security products that are no longer supported by vendors are removed.</p>	<p>hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products are applied within <b>two weeks</b> of release.</p> <p><b>Patches, updates or vendor mitigations for vulnerabilities in other applications are applied within one month of release.</b></p> <p>Internet-facing services, office productivity suites, web browsers and their extensions, email clients, PDF</p>	<p>Patches, updates or vendor mitigations for vulnerabilities in office productivity suites, web browsers and their extensions, email clients, PDF software, and security products are applied within two weeks of release, <b>or within 48 hours if an exploit exists.</b></p> <p>Patches, updates or vendor mitigations for vulnerabilities in other applications are applied within one month of release.</p> <p><b>Applications</b> that are no longer supported by vendors are removed.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
		supported by vendors are removed.	
<p><b>Configure Microsoft Office macro settings</b></p>	<p>Microsoft Office macros are disabled for users that do not have a demonstrated business requirement.</p> <p>Microsoft Office macros in files originating from the internet are blocked.</p> <p>Microsoft Office macro antivirus scanning is enabled.</p> <p>Microsoft Office macro security settings cannot be changed by users.</p>	<p>Microsoft Office macros are disabled for users that do not have a demonstrated business requirement.</p> <p>Microsoft Office macros in files originating from the internet are blocked.</p> <p>Microsoft Office macro antivirus scanning is enabled.</p> <p><b>Microsoft Office macros are blocked from making Win32 API calls.</b></p> <p>Microsoft Office macro security</p>	<p>Microsoft Office macros are disabled for users that do not have a demonstrated business requirement.</p> <p><b>Only Microsoft Office macros running from within a sandboxed environment, a Trusted Location or that are digitally signed by a trusted publisher are allowed to execute.</b></p> <p><b>Only privileged users responsible for validating that Microsoft Office macros are free of malicious code can write to and modify content within</b></p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
		<p><b>Allowed and blocked Microsoft Office macro execution events are logged.</b></p>	<p><b>signed by an untrusted publisher cannot be enabled via the Message Bar or Backstage View.</b></p> <p><b>Microsoft Office's list of trusted publishers is validated on an annual or more frequent basis.</b></p> <p>Microsoft Office macros in files originating from the internet are blocked.</p> <p>Microsoft Office macro antivirus scanning is enabled.</p> <p>Microsoft Office macros are blocked from making Win32 API calls.</p> <p>Microsoft Office macro security settings cannot be</p>

Report a cybercrime, cyber security incident or vulnerability.



Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
			<p>macro execution events are <b>centrally</b> logged.</p> <p><b>Event logs are protected from unauthorised modification and deletion.</b></p> <p><b>Event logs are monitored for signs of compromise and actioned when any signs of compromise are detected.</b></p>
<p><b>User application hardening</b></p>	<p>Web browsers do not process Java from the internet.</p> <p>Web browsers do not process web advertisements from the internet.</p> <p>Internet Explorer 11 does not process</p>	<p>Web browsers do not process Java from the internet.</p> <p>Web browsers do not process web advertisements from the internet.</p> <p>Internet Explorer 11 does not process</p>	<p>Web browsers do not process Java from the internet.</p> <p>Web browsers do not process web advertisements from the internet.</p> <p>Internet Explorer 11 <b>is disabled or</b></p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
	<p>Web browser security settings cannot be changed by users.</p>	<p>Web browser security settings cannot be changed by users.</p> <p><b>Microsoft Office is blocked from creating child processes.</b></p> <p><b>Microsoft Office is blocked from creating executable content.</b></p> <p><b>Microsoft Office is blocked from injecting code into other processes.</b></p> <p><b>Microsoft Office is configured to prevent activation of OLE packages.</b></p> <p><b>Microsoft Office security settings cannot be changed by users.</b></p>	<p>changed by users.</p> <p>Microsoft Office is blocked from creating child processes.</p> <p>Microsoft Office is blocked from creating executable content.</p> <p>Microsoft Office is blocked from injecting code into other processes.</p> <p>Microsoft Office is configured to prevent activation of OLE packages.</p> <p>Microsoft Office security settings cannot be changed by users.</p> <p>PDF software is blocked from creating child processes.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
		<p><b>creating child processes.</b></p> <p><b>PDF software security settings cannot be changed by users.</b></p> <p><b>ACSC or vendor hardening guidance for web browsers, Microsoft Office and PDF software is implemented.</b></p> <p><b>Blocked PowerShell script execution events are logged.</b></p>	<p>changed by users.</p> <p>ACSC or vendor hardening guidance for web browsers, Microsoft Office and PDF software is implemented.</p> <p><b>.NET Framework 3.5 (includes .NET 2.0 and 3.0) is disabled or removed.</b></p> <p><b>Windows PowerShell 2.0 is disabled or removed.</b></p> <p><b>PowerShell is configured to use Constrained Language Mode.</b></p> <p>Blocked PowerShell script execution events are <b>centrally</b> logged.</p> <p><b>Event logs are</b> <b>protected from</b></p>

Report a cybercrime, cyber security incident or vulnerability.



Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
			<p><b>Event logs are monitored for signs of compromise and actioned when any signs of compromise are detected.</b></p>
<p><b>Restrict administrative privileges</b></p>	<p>Requests for privileged access to systems and applications are validated when first requested.</p> <p>Privileged accounts (excluding privileged service accounts) are prevented from accessing the internet, email and web services.</p> <p>Privileged users use separate privileged and unprivileged operating environments.</p>	<p>Requests for privileged access to systems and applications are validated when first requested.</p> <p><b>Privileged access to systems and applications is automatically disabled after 12 months unless revalidated.</b></p> <p><b>Privileged access to systems and applications is automatically disabled after 45 days of inactivity.</b></p>	<p>Requests for privileged access to systems and applications are validated when first requested.</p> <p>Privileged access to systems and applications is automatically disabled after 12 months unless revalidated.</p> <p>Privileged access to systems and applications is automatically disabled after 45 days of inactivity.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
	<p>operating environments.</p> <p>Privileged accounts (excluding local administrator accounts) cannot logon to unprivileged operating environments.</p>	<p>are prevented from accessing the internet, email and web services.</p> <p>Privileged users use separate privileged and unprivileged operating environments.</p> <p><b>Privileged operating environments are not virtualised within unprivileged operating environments.</b></p> <p>Unprivileged accounts cannot logon to privileged operating environments.</p> <p>Privileged accounts (excluding local administrator accounts) cannot logon to</p>	<p><b>limited to only what is required for users and services to undertake their duties.</b></p> <p><b>Privileged accounts</b> are prevented from accessing the internet, email and web services.</p> <p>Privileged users use separate privileged and unprivileged operating environments.</p> <p>Privileged operating environments are not virtualised within unprivileged operating environments.</p> <p>Unprivileged accounts cannot logon to privileged operating environments.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
		<p><b>Administrative activities are conducted through jump servers.</b></p> <p><b>Credentials for local administrator accounts and service accounts are long, unique, unpredictable and managed.</b></p> <p><b>Privileged access events are logged.</b></p> <p><b>Privileged account and group management events are logged.</b></p>	<p>accounts) cannot logon to unprivileged operating environments.</p> <p><b>Just-in-time administration is used for administering systems and applications.</b></p> <p>Administrative activities are conducted through jump servers.</p> <p>Credentials for local administrator accounts and service accounts are long, unique, unpredictable and managed.</p> <p><b>Windows Defender Credential Guard and Windows Defender Remote Credential Guard</b></p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
			<p>logged.</p> <p>Privileged account and group management events are <b>centrally</b> logged.</p> <p><b>Event logs are protected from unauthorised modification and deletion.</b></p> <p><b>Event logs are monitored for signs of compromise and actioned when any signs of compromise are detected.</b></p>
<p><b>Patch operating systems</b></p>	<p>An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability</p>	<p>An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability</p>	<p>An automated method of asset discovery is used at least fortnightly to support the detection of assets for subsequent vulnerability scanning</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
	<p>to-date vulnerability database is used for vulnerability scanning activities.</p> <p>A vulnerability scanner is used at least daily to identify missing patches or updates for vulnerabilities in operating systems of internet-facing services.</p> <p>A vulnerability scanner is used at least fortnightly to identify missing patches or updates for vulnerabilities in operating systems of workstations, servers and network devices.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of internet-facing</p>	<p>to-date vulnerability database is used for vulnerability scanning activities.</p> <p>A vulnerability scanner is used at least daily to identify missing patches or updates for vulnerabilities in operating systems of internet-facing services.</p> <p>A vulnerability scanner is used at least <b>weekly</b> to identify missing patches or updates for vulnerabilities in operating systems of workstations, servers and network devices.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of</p>	<p>to-date vulnerability database is used for vulnerability scanning activities.</p> <p>A vulnerability scanner is used at least daily to identify missing patches or updates for vulnerabilities in operating systems of internet-facing services.</p> <p>A vulnerability scanner is used at least weekly to identify missing patches or updates for vulnerabilities in operating systems of workstations, servers and network devices.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of internet-facing</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
	<p>hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of workstations, servers and network devices are applied within one month of release.</p> <p>Operating systems that are no longer supported by vendors are replaced.</p>	<p>hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of workstations, servers and network devices are applied within <b>two weeks</b> of release.</p> <p>Operating systems that are no longer supported by vendors are replaced.</p>	<p>hours if an exploit exists.</p> <p>Patches, updates or vendor mitigations for vulnerabilities in operating systems of workstations, servers and network devices are applied within two weeks of release, <b>or within 48 hours if an exploit exists.</b></p> <p><b>The latest release, or the previous release, of operating systems are used.</b></p> <p>Operating systems that are no longer supported by vendors are replaced.</p>
<p><b>Multi-factor authentication</b></p>	<p>Multi-factor authentication is used by an organisation's users</p>	<p>Multi-factor authentication is used by an organisation's users</p>	<p>Multi-factor authentication is used by an organisation's users</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
	<p>internet-facing services.</p> <p>Multi-factor authentication is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their organisation's sensitive data.</p> <p>Multi-factor authentication (where available) is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their organisation's non-sensitive data.</p>	<p>internet-facing services.</p> <p>Multi-factor authentication is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their organisation's sensitive data.</p> <p>Multi-factor authentication (where available) is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their organisation's non-sensitive data.</p>	<p>internet-facing services.</p> <p>Multi-factor authentication is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their organisation's sensitive data.</p> <p>Multi-factor authentication (where available) is used by an organisation's users when they authenticate to third-party internet-facing services that process, store or communicate their organisation's non-sensitive data.</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
	<p>non-organisational users (but they can choose to opt out) when they authenticate to the organisation's internet-facing services.</p>	<p>non-organisational users (but they can choose to opt out) when they authenticate to the organisation's internet-facing services.</p> <p><b>Multi-factor authentication is used to authenticate privileged users of systems.</b></p> <p><b>Multi-factor authentication uses either: something users have and something users know, or something users have that is unlocked by something users know or are.</b></p> <p><b>Successful and</b></p>	<p>non-organisational users (but they can choose to opt out) when they authenticate to the organisation's internet-facing services.</p> <p>Multi-factor authentication is used to authenticate privileged users of systems.</p> <p><b>Multi-factor authentication is used to authenticate users accessing important data repositories.</b></p> <p>Multi-factor authentication is <b>phishing-resistant and</b> uses either: something users have and something users know, or something</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Successful and <b>Maturity Level Three</b> unsuccessful multi-factor authentication
			<p>events are <b>centrally</b> logged.</p> <p><b>Event logs are protected from unauthorised modification and deletion.</b></p> <p><b>Event logs are monitored for signs of compromise and actioned when any signs of compromise are detected.</b></p>
<b>Regular backups</b>	Backups of important data, software and configuration settings are performed and retained with a frequency and retention timeframe in accordance with business continuity requirements.	Backups of important data, software and configuration settings are performed and retained with a frequency and retention timeframe in accordance with business continuity requirements.	<p>Backups of important data, software and configuration settings are performed and retained with a frequency and retention timeframe in accordance with business continuity requirements.</p> <p>Backups of important</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	Maturity Level Two	Maturity Level Three
	<p>synchronised to enable restoration to a common point in time.</p> <p>Backups of important data, software and configuration settings are retained in a secure and resilient manner.</p> <p>Restoration of important data, software and configuration settings from backups to a common point in time is tested as part of disaster recovery exercises.</p> <p>Unprivileged accounts cannot access backups belonging to other accounts.</p> <p>Unprivileged</p>	<p>configuration settings are synchronised to enable restoration to a common point in time.</p> <p>Backups of important data, software and configuration settings are retained in a secure and resilient manner.</p> <p>Restoration of important data, software and configuration settings from backups to a common point in time is tested as part of disaster recovery exercises.</p> <p>Unprivileged accounts cannot access backups belonging to other</p>	<p>a common point in time.</p> <p>Backups of important data, software and configuration settings are retained in a secure and resilient manner.</p> <p>Restoration of important data, software and configuration settings from backups to a common point in time is tested as part of disaster recovery exercises.</p> <p>Unprivileged accounts cannot access backups belonging to other accounts, <b>nor their own accounts.</b></p> <p>Privileged accounts (excluding backup administrator</p>

Report a cybercrime, cyber security incident or vulnerability.



Report

Strategy	Maturity Level One	<b>(excluding backup Maturity Level Two administrator accounts) cannot</b>	<b>accounts, nor their Maturity Level Three own accounts.</b>
		<p><b>access backups belonging to other accounts.</b></p> <p>Unprivileged accounts are prevented from modifying and deleting backups.</p> <p><b>Privileged accounts (excluding backup administrator accounts) are prevented from modifying and deleting backups.</b></p>	<p>Unprivileged accounts are prevented from modifying and deleting backups.</p> <p>Privileged accounts (<b>including</b> backup administrator accounts) are prevented from modifying and deleting backups <b>during their retention period.</b></p>

## Was this information helpful?

 Report a cybercrime, cyber security incident or vulnerability.





Get alerts on new threats  
**Alert Service**



Become an  
**ACSC Partner**



Report a cybercrime or cyber security incident

### Acknowledgement of Country

*We acknowledge the Traditional Owners and Custodians of Country throughout Australia and their continuing connections to land, sea and communities. We pay our respects to them, their cultures and their Elders; past, present and emerging. We also recognise Australia's First Peoples' enduring contribution to Australia's national security.*

[About the ACSC](#)

[Alerts and advisories](#)

[News and media](#)

[View all content](#)

[Contact us](#)

[Careers](#)

[Accessibility](#)

[Copyright](#)

[Disclaimer](#)

[Privacy](#)

[Social media terms of use](#)

## Australian Cyber Security Hotline

**1300 CYBER1** (1300 292 371)

Report a cybercrime, cyber security incident or vulnerability.



**Report**

Authorised by the Australian Government, Canberra